

TIB KAT[®] 218

TIB KAT 218 is a versatile multi-purpose catalyst for many applications like:

- Esterification and transesterification reactions between 80 – 240°C at concentrations between 0.01 – 1 wt.-%,
- Polyurethane systems as
 - can & coil coatings, car refinishing, architectural coatings and other industrial coatings
 - 1 - and 2-comp. – adhesives & sealants
 - Elastomers
- Silicones & silane crosslinking, especially for 1- and 2-component RTV silicones
- Crosslinking of silane modified polyolefines (XPE)

Upon request, **TIB KAT 218** can also be offered in special formulations.

Product Data	
Chemical name	Dibutyltinlaurate (DBTL)
CAS No.	77-58-7
Appearance	clear liquid
Melting point	approx. 10 - 15°C

Specification

Tin content	≥ 17.5 %
Density (20°C)	1.03 - 1.06 g/cm ³
Colour (Gardner)	≤ 3

Storage

TIB KAT 218 can be stored at least one year if kept closed in the original packaging; sensitive to frost.

Packaging

220 kg drum,
other packaging size upon request.

Special advice for security

Information concerning

- classification and labelling according to the regulations governing transport and hazardous chemicals
- protective measures for storage and handling
- safety measures in case of accident and fire
- toxicity and ecological effects

is given in our material safety data sheet.

Customs Tariff No.: 2931 9000

Issue / May 23