

TIB KAT[®] 226

TIB KAT 226 finds its use in the following applications:

- catalyst for synthesis of polyurethan-systems
- catalyst for polycondensation reactions of RTV silicon resins and of silanes
- catalyst for 1 component MS Silyl systems

TIB KAT 226 is miscible with organic solvents, but sensitive to moisture. **TIB KAT 226** is available in special formulations upon request.

As **TIB KAT 226** is sensitive to moisture, immediate sealing of once opened drums is advised and inertisation with nitrogen is recommended.

Product data

Chemical name	Dibutyltindiketanoate
CAS No.	22673-19-4
Molecular weight	431.1 g/mol
State of aggregation	liquid

Specification

Tin content	≥ 26.0 %
Colour (Gardner)	≤ 5
Density (20°C)	1.20 - 1.30 g/cm ³

Storage

TIB KAT[®] 226 can be stored for at least one year if kept closed in the original packaging. Sensitive to frost and moisture.

Packaging

200 kg plastic drum and 1.000 kg ICB, other packaging size upon request.

Special advice for security

Information concerning

- classification and labelling according to the regulations governing transport and hazardous chemicals
- protective measures for storage and handling
- safety measures in case of accident and fire
- toxicity and ecological effects

is given in our material safety data sheet.

Customs Tariff No.: 29319000

Issue / Jan 17

TIB Chemicals AG | Mülheimer Strasse 16 -22 | D-68219 Mannheim | P.O. Box 81 02 20 | D-68202 Mannheim
Phone +49 (0) 621 8901- 811 | Fax +49 (0) 621 8901- 475 | info.@tib-chemicals.com | www.tib-chemicals.com

*This information is given to the best of our knowledge but without obligation. We are not liable for any wrong advice or any advice we may have failed to give.
This data sheet becomes invalid as soon as a new edition has been published. Please contact us for latest.*

