

TIB KAT[®] 233

TIB KAT 233 is used for following purposes:

- catalyst for synthesis of polyurethan-systems
- catalyst for transesterification reactions of acrylics, oleochemicals and other esters
- catalyst for polycondensation reactions of RTV silicon resins and of silanes
- catalyst for the production of raw material for polycarbonates

Storage

TIB KAT 233 can be stored for at least one year if kept closed in the original packaging. Sensitive to frost and slightly sensitive to moisture.

Packaging

200 kg plastic drum,
other packaging size upon request.

Special advice for security

Information concerning

- classification and labelling according to the regulations governing transport and hazardous chemicals
- protective measures for storage and handling
- safety measures in case of accident and fire
- toxicity and ecological effects

is given in our material safety data sheet.

Customs Tariff No.: 2931 9000

Product data	
Chemical name	Dibutyltindiacetate (DBTA)
CAS No.	1067-33-0
Molecular weight	351.01 g/mol
Appearance	clear liquid
Melting point	< 12 °C

Specification	
Tin content	32,5 - 34,0 %
Density (20 ⁰ C)	1,25 - 1,40 g/cm ³
Colour (Gardner)	≤ 3

Issue / Oct 16

TIB Chemicals AG | Mülheimer Strasse 16 -22| D-68219 Mannheim| P.O. Box 81 02 20| D-68202 Mannheim
Phone +49 (0) 621 8901- 811| Fax +49 (0) 621 8901- 475| info.@tib-chemicals.com| www.tib-chemicals.com

*This information is given to the best of our knowledge but without obligation. We are not liable for any wrong advice or any advice we may have failed to give.
This data sheet becomes invalid as soon as a new edition has been published. Please contact us for latest.*

