

TIB KAT[®] 517

TIB KAT 517 is a liquid catalyst based on an organo-titanate chelate.

TIB KAT 517 can be applied mainly for the curing of silicones, silanes and silane terminated polymer systems, especially for

- MS / STP / STPU polymer systems
- curing of RTV-silicones

TIB KAT 517 is sensitive to moisture and therefore contact has to be minimized. At higher humidity weather conditions hydrolyses can be occur and leads to decreasing flash points.

Product data

Chemical description	Ethylacetoacetate titanate
Appearance	yellow-to-red clear liquid
Solubility	miscible in most organic solvents – hydrolysis in water

Specification

Ti content (as TiO ₂ cont.)	≥ 16.0 wt.-%
Density (20 ⁰ C)	1.070 – 1.090 g/cm ³

Storage

TIB KAT 517 can be stored at least 12 months from date of delivery if kept closed in the original packaging at ambient temperature and in a dry place protected against temperature raise and excessive of humidity. Intertisation of once opened drums with nitrogen is recommended.

Packaging

50 kg can and 200 kg drum,
other packaging size upon request.

Special advice for security

Information concerning

- classification and labelling according to the regulations governing transport and hazardous chemicals
- protective measures for storage and handling
- safety measures in case of accident and fire
- toxicity and ecological effects

is given in our material safety data sheet.

Customs Tariff No.: 29319000

Issue / Jan 17

TIB Chemicals AG | Mülheimer Strasse 16 -22 | D-68219 Mannheim | P.O. Box 81 02 20 | D-68202 Mannheim
Phone +49 (0) 621 8901- 811 | Fax +49 (0) 621 8901- 475 | info.@tib-chemicals.com | www.tib-chemicals.com

This information is given to the best of our knowledge but without obligation. We are not liable for any wrong advice or any advice we may have failed to give. This data sheet becomes invalid as soon as a new edition has been published. Please contact us for latest.

