

## TIB KAT<sup>®</sup> 724

**TIB KAT 724** finds its use in the following application

- catalyst for curing of polyurethanes
- catalyst for 2K PU systems

**TIB KAT 724** is slightly sensitive to moisture.

---

### Product Data

Description	Metal based catalyst
Appearance	Clear liquid at RT /25°C

### Typical data

Metal content	19,0-21,0 %
Colour (Gardner)	≤ 6
Density	1,050 – 1,250g/ml

### Storage

**TIB KAT 724** can be stored for at least half a year if kept closed in the original packaging. Sensitive to frost.

### Packaging

200 kg plastic drum, 1000kg IBC  
other packaging size upon request.

### Special advice for security

Information concerning

- classification and labelling according to the regulations governing transport and hazardous chemicals
- protective measures for storage and handling
- safety measures in case of accident and fire
- toxicity and ecological effects

is given in our material safety data sheet.

**Customs Tariff No.: 38159090**

Issue 1 / Dec 2020



TIB Chemicals AG | Mülheimer Strasse 16 -22 | D-68219 Mannheim | P.O. Box 81 02 20 | D-68202 Mannheim  
Phone +49 (0) 621 8901- 811 | Fax +49 (0) 621 8901- 475 | info.@tib-chemicals.com | www.tib-chemicals.com

*This information is given to the best of our knowledge but without obligation. We are not liable for any wrong advice or any advice we may have failed to give.  
This data sheet becomes invalid as soon as a new edition has been published. Please contact us for latest.*