

TIB KAT[®] 324

TIB KAT 324 is a liquid organotin catalyst dissolved in a high boiling solvent.

TIB KAT 324 is especially advantageous for the production of coatings based on polyurethanes, because it shows a high degree of compatibility in the formulation.

TIB KAT 324 is suitable for the condensation of silicones, especially for the production of RTV silicone resins.

Concentrations between 0.01 – 1 wt.-% according to the application have been proved as advantageous.

Product data

Formula	proprietary
State of aggregation	liquid
Density	approx. 1.07 – 1.08 g/cm ³

Specification

Tin content	≥ 20 wt.-%
Colour (Gardner)	< 5

Storage

TIB KAT 324 can be stored at least one year if kept closed in the original packaging. Sensitive to frost.

Packaging

200 kg drum,
other packaging size upon request.

Special advice for security

Information concerning:

- classification and labelling according to the regulations governing transport and hazardous chemicals
 - protective measures for storage and handling
 - safety measures in case of accident and fire
 - toxicity and ecological effects
- is given in our material safety data sheet.

Customs Tariff No.: 3815 90 90

Issue / Oct 16

TIB Chemicals AG | Mülheimer Strasse 16 -22 | D-68219 Mannheim | P.O. Box 81 02 20 | D-68202 Mannheim
Phone +49 (0) 621 8901- 811 | Fax +49 (0) 621 8901- 475 | info.@tib-chemicals.com | www.tib-chemicals.com

*This information is given to the best of our knowledge but without obligation. We are not liable for any wrong advice or any advice we may have failed to give.
This data sheet becomes invalid as soon as a new edition has been published. Please contact us for latest.*

