

TIB KAT® 618

TIB KAT® 618 is an effective catalyst for numerous applications.

TIB KAT® 618 is especially suitable for various applications in the catalysis of polyurethane systems. Compared to organotin catalysts **TIB KAT® 618** shows a lower activity offering longer pot life in 2p systems.

TIB KAT® 618 is typically used in concentrations between 0.02 - 1 wt.-% in relation to the total formulation.

Product Data	
Chemical formula	Zinc octoate formulation
State of aggregation	Clear liquid
Typical Data	
Zinc content	17.0 – 18.5 %
Colour (Gardner)	≤ 5

Storage

TIB KAT® 618 can be stored for at least one year if kept closed in the original packaging.

Packaging

200 kg drum, 25 kg drum
other packaging size upon request.

Special advice for security

Information concerning

- classification and labelling according to the regulations governing transport and hazardous chemicals
- protective measures for storage and handling
- safety measures in case of accident and fire
- toxicity and ecological effects

is given in our material safety data sheet.

Customs Tariff No.: 381590 90 00

Issue 1 / Apr 23

TIB Chemicals AG | Mülheimer Strasse 16 -22| D-68219 Mannheim| P.O. Box 81 02 20| D-68202 Mannheim
Phone +49 (0) 621 8901- 811| Fax +49 (0) 621 8901- 475| info.@tib-chemicals.com| www.tib-chemicals.com

This information is given to the best of our knowledge but without obligation. We are not liable for any wrong advice or any advice we may have failed to give. This data sheet becomes invalid as soon as a new edition has been published. Please contact us for latest.

