



TIB Stanal DG

Properties

- ◆ liquid
- ◆ low alkaline
- ◆ free of silicates
- ◆ free or surfactants
- ◆ recyclable, also in combination with TIB Stanal DG-B
- ◆ suitable for steel, partly suitable for brass, copper and aluminum

Product Data

Chemical composition	aqueous formulation, contains phosphates
Delivery form	liquid
Color	colorless or slightly yellowish
pH value (10 g/l)	10-11
Density (20°C)	1.66 kg/l approx.

Application

TIB Stanal DG is suitable in combination with the detergent booster **TIB Stanal DG-B** for cleaning in soak and ultrasonic applications. Oil, grease and pigments are removable without problems.

concentration: 1.5-6% vol. **TIB Stanal DG** (corresponds to 25-100 g/l) + 0.2-1% vol. surfactant booster **TIB Stanal DG-B**

temperature: 40-90°C

application time: 0.5-10 min

Storage

TIB Stanal DG has a shelf life of min. 12 months, if stored correctly in dry areas and in its original closed packaging at room temperature.

Packaging

Standard packaging
PE can

volume [l]	25
gross/net [kg]	36,3/30

Special advices for security

Information concerning

- ◆ classification and labelling according to the regulations governing transport and hazardous chemicals.
- ◆ protective measures for storage and handling
- ◆ safety measures in case of accident and fire
- ◆ toxicity and ecological effects

is given in our material safety data sheets.

Customs Tariff Number

3402 9090