



## TIB KAT 316

### Description

*TIB KAT 316* (Diocetyl tin bis-(2-Ethylhexyl Mercaptoacetate)), also known as DOTE, is octyl-based dialkyl organotin with added functionality. *TIB KAT 316* has the characteristic reactivity of a Sn (IV) organotin catalyst with improved upfront delay and an improved hydrolytic stability due to the presence of a ligand with sulfur functionality.

Unlike standard organotin carboxylates, sulfur-bearing organotins are primarily used as a catalyst for polyurethanes. The reactivity of catalysts such as *TIB KAT 316* tend to be inactive in silicone and esterification-related applications. As the sulfur ligand acts as a blocking agent, thermal deblocking is required to initiate the back-end cure. Thus, catalysts such as *TIB KAT 316* tend to perform best in adhesive, elastomer, and foam applications with adequate exotherms. For coatings applications, *TIB KAT 316* can be used in baked cured systems in contrast to ambient cured systems.

*TIB KAT 316* is not available in Europe.

### Product Data

Chemical name	Diocetyl tin bis-(2-ethylhexyl mercaptoacetate)
CAS No.	15571-58-1
Molecular weight	751.80 g/mol
State of aggregation	liquid

### Specification

Tin content	15.2 – 17.0 %
Density (20°C)	1.02 – 1.10 g/cm <sup>3</sup>
Colour (Gardner)	≤ 5

### Storage

*TIB KAT 316* should be stored in the original packaging at moderate temperatures and kept from freezing. The container should be closed tightly after each use to maximize shelf life. Although more stable compared to organotin carboxylates, longterm contact with moisture could result in hydrolysis with the formation of tin oxide insolubles leading to deactivation of *TIB KAT 316*.

### Packaging

Packaging size upon request.

### Packaging USA





44 lb (20 kg) pails,

440 lb (200 kg) plastic drums,

other packaging size upon request.

### Special advice for Security

Information concerning

-  classification and labelling according to the regulations governing transport and hazardous chemicals
-  protective measures for storage and handling
-  safety measures in case of accident and fire
-  toxicity and ecological effects

is given in our material safety data sheet.

**Customs Tariff No.: 3815 9090**



## TIB KAT 316

### Product Carbon Footprint (PCF)

Created by: KlimAktiv Consulting GmbH

PCF-results (emissions)	Value (Mannheim)	Value (Pittsburgh)	Unit
<b>Sum of PCFs (Cradle-to-gate)</b>	-	-	kg CO <sub>2</sub> eq/kg
<b>PCF excluding biogenic emissions</b>	-	-	kg CO <sub>2</sub> eq/kg
<b>Biogenic emissions</b>	-	-	kg CO <sub>2</sub> eq/kg

The Product Carbon Footprint (PCF) covers one of several environmental impacts of chemical products. The PCF does not allow comprehensive conclusions about the overall environmental performance of the product. Comparisons of PCFs from different data sources are only possible to a limited extent. The PCF presented here applies to the product sold by TIB Chemicals.

The PCF is based on data of the accounting year 2024 and follows the calculation method outlined in ISO 14067, the Tfs Guideline, the BASF Guideline, the cradle-to-gate system boundaries, the declared unit kg CO<sub>2</sub>e/kg product (excl. packaging) and the sum of different emissions from Scope 1, 2 and 3 (raw material and preliminary products (e.g. secondary data), transportation of purchased products and inbound logistics, as well as company- and site-specific processes including primary energy consumption, electricity and heat consumption). The emissions from biogenic carbon and land-use changes are considered as far as data sources are available.